

EX-222.3 Stereo Integrated Amplifier 2x70W - Wireless

HIGHLIGHTS

- ✓ Wireless
- ✓ Coaxial and optic inputs
- ✓ MP3 input
- ✓ Headphone output
- ✓ pré-out output
- ✓ 2x toroidal transformers
- ✓ Power output for optional card

LOGISTICAL DATA

EAN Code
Black: 0634654606112

DEEE
4.4 = 0,84 € H.T. = 1 € T.T.C.

Dimensions (WxHxD) & Weight PRODUCT
430 x 80 x 340 mm / 8.3 Kg

PACKAGING
490 x 140 x 420 mm / 8.9 Kg



This amplifier EX-222.3 was designed in an audiophile approach to ensure the high fidelity amater a faithful reproduction of his favourite music. It delivers 2x70W RMS into 8Ω, thanks to its high-performance 2x200 VA Toroidal transformers.

It includes a WIRELESS interface, allowing you to play music from your Smartphones. The EX-222.3 comes with 4 unbalanced audio inputs including a 3,5 mini jack MP3 input, one digital input (coaxial and/or optical) allowing connection to latest generation TV sets.

Finally, it provides a « pre-out » to perform bi-amplification.

MAIN FEATURES

- High quality manufacturin
- Shielded preamplifier
- 2 transformers for best power
- Large power output amplifier stage for both channels (220VA)
- Stage power generously dimensioned consequences: ability to drive any kind of speakers (8, 4, 2 Ohms).
- WIRELESS with removable antenna
- Optical and Coaxial digital inputs
- MP3 input 3,5mm
- Headphone output 6.35mm
- Power output for optional card (eg. The Phono card EX-PHONO-2X)

DAC: The S/PDIF input is interfaced to a Cirrus Logic CS8415 chip and analog digital conversion is supported by a CS4334 circuit from the same manufacturer. Maximum sampling is 24 bits at 96 kHz on the coaxial and optical inputs.

Digital Inputs: The OPTICAL connector will override the source connected to COAXIAL, unless the source connected to the optical connector is turned off. In this case, you can listen to the source connected in coaxial.

SPECIFICATIONS

Amplifier section

Power: 2x70W RMS into 8 Ω
and 2x120W into 4 Ω
Total harmonic distortion < 0,01%
Signal to noise ratio > 100 dBA
Bandwidth: 20 Hz - 20 KHz
Speaker Impedance Compatibility
Range : 3-8 Ω

Wireless

Range: about 10 m

Connectors

3x RCA line inputs
1x Digital input: Optical and Coaxial
1x MP3 input (Mini-jack 3.5 mm)
1x RCA line output: Pre-Out
1x Headphone Jack 6.35 mm in front
1x Power output for optional card (Type 2X)
4x Screw terminals compatible with banana plugs
1x Detachable IEC power cord
1x Remote control: RC-EX1.2

Included Accessories

1x Detachable IEC power cord
1x Wireless antenna
1x Remote control RC-EX1.2
1x Battery CR2025
1x Manual